

GEN 2.10 SPECIFICATIONS OF STARTING-UNITS

ELECTRICAL STARTING-UNITS

Equivalent to:

		U.S.FLIP	U.K.FLIP
A-3AE	DC 28, 5 V (24 V), 22 KW, max 28,5 V, 40 KW	A-3/A-7	E 26/E 27/ E28
C-26B	DC 28 V, 45 KW AC 115/200 V, 15 KVA single phases 400 cycles.		
MD-3 or MD-3A	DC 28 V, 45 KW AC 115/200 V, 15 KVA 3 phases 400 cycles.		E 45/E 46
IMPERIA	DC 28 V, 200 A, 5,6 KW AC 115/200 V, 10 KVA 3 phases 400 cycles.		
ERNST	20 KVA and 45 KVA 115/280 V, 400 Hz, 10 KW 28 V DC.		
HOUCHIN	10 KVA 115/200 V, 28 V DC 400 Hz		
AIR STARTING-UNITS			
TMC 85-9	45 PSI 90 LBS per min	MA-1A	A 27/A 39
RFT-90	38 PSI, 124 LBS	A 2	MA-1A A 39
AIR PARTNER (MA2 or M7)	35 PASI, 110 LBS per min.	AC-35	
AIR CONDITIONER			
HOKANSSON	DC 28 V, 4 AMP, 115/208 V, 10 KVA, 3 phases 400 cycles		

BLANK